

# Console Wall Charger + Phone Holder

## USER GUIDE



### Specifications

2 USB Charging Ports + 2 AC Outlets  
Input: 100-240vac 50/60HZ  
Output:  
AC: 120Vac/10A (1.2KW)  
USB1: 5V/2.1A  
USB2: 5V/2.1A  
USB Total Output: 5V/2.1A max

### Additional Features

- Phone Holder on top allows you to place your phone on the Console while charging.
- Night Lamp automatically detects when the environment is dark and turns on. The Night Lamp will automatically turn off when it detects the environment is bright.

### Using the charger

1. Plug the Console into a wall outlet.
2. Use suitable charging cables, charge your devices by either the USB ports or the AC outlets.
3. When both USB ports are in use, a total 2.1A of output power will be divided among the ports. The Console will automatically detect each device and provide the optimal charging power.
4. Surge protection safety will shut down the Console if it detects that the output power needed to charge your devices exceeds 2.1A. If this occurs, you will need to unplug one device until the power needed to charge the remaining device is less than 2.1A.

### Safety Precautions

- Do not crush, disassemble, puncture, expose to fire, or short external contacts.
- Keep the Console dry at all times to prevent corrosion of electronic circuits.
- Do not store the Console in dusty or dirty areas.
- Do not expose the Console to extreme hot or cold temperatures. Heat can warp/melt the components & shorten product life, while cold can cause moisture to form inside and damage the electronic circuit board.
- Do not use harsh chemicals, cleaning solvents, or strong detergents to clean the Console.
- Do not drop, or shake the Console. Rough handling may break the internal circuit board.
- Do not modify, re-manufacture or attempt to insert foreign objects into the Console.
- Do not immerse or expose to liquids, explosions or other hazards.



FSC  
www.fsc.org

MIX  
Packaging from  
responsible sources

FSC® C167708